(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 16 December 2004 (16.12.2004)

PCT

(10) International Publication Number WO 2004/109311 A1

(51) International Patent Classification7:

(21) International Application Number:

PCT/NZ2004/000117

G01R 31/36

(22) International Filing Date: 3 June 2004 (03.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 526320

6 June 2003 (06.06.2003) NZ

(71) Applicant (for all designated States except US): INVEN-SYS ENERGY SYSTEMS (NZ) LIMITED [NZ/NZ]; 39 Princess Street, Christchurch, 8004 (NZ).


(72) Inventors; and

(75) Inventors/Applicants (for US only): AL-ANBUKY, Adnan, H [NZ/NZ]; 27 Stableford Green, Christchurch (NZ). PASCOE, Phillip, E [NZ/NZ]; 28 Maidstone Road, Christchurch (NZ). (74) Agent: BALDWIN SHELSTON WATERS; PO Box 852, Wellington, 6001 (NZ).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHODS AND APPARATUS FOR BATTERY MONITORING, CHARACTERISATION AND RESERVE TIME ESTIMATION



(57) Abstract: A method of battery monitoring including the steps of: acquiring a battery voltage measurement from the battery; and acquiring a time measurement associated with the battery voltage measurement. A scaled voltage value is determined by scaling the battery voltage measurement with respect to a start voltage and/or predetermined end voltage. A scaled time value is determined from the scaled voltage value in accordance with a predetermined battery characteristic. An absolute reserve time value is then obtained from the scaled time value, the reserve time being indicative of the difference between the time measurement and an end time associated with the predetermined end voltage.

2004/109311 A1

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.